



KRIMPKOUS

3:1 DUBBELWANDIG

UITVOERING MET LIJM



Deze universeel toepasbare krimpkous MET LIJM voldoet aan de MIL en UL 224 specificaties en is geschikt voor zeer vele protectie-, bundeling- en isolatietoepassingen. Beschikbaar in verschillende verpakkingsvormen. De smeltlijm zal bij verwarming het te beschermen stuk inkapselen en een uitstekende bescherming bieden tegen vocht en vloeistoffen.

	Test methods	Specifications
SHRINK TEMPERATURE	UL 224	110°C
OPERATING TEMPERATURE RANGE	UL 224	-55°C-125°C
RADIAL SHRINKING RATIO	UL 224	≥ 50%
LONGITUDINAL CHANGE	UL 224	≤ 10%
TENSILE STRENGTH (MPA)	ASTM 2671	≥ 10.4
ELONGATION AT BREAK	ASTM 2671	≥ 200%
TENSILE STRENGTH AFTER AGING (MPA)	ASTM 2671	≥ 7.3
ELONGATION AT BREAK AFTER AGING	ASTM 2671	≥ 100%
AGING IN CIRCULATING-AIR OVEN	158°C ± 1°C, 168 hrs	No break
VOLUME RESISTANCE (Ω.CM)	ASTM 876	≥ 10 ¹³
DIELECTRIC STRENGTH (KV/MM)	ASTM 2671, AC 250V, 1 min	≥ 15.0
WATER ABSORPTION	ASTM 570	less than 0.4%
FLUID RESISTANCE	UL 224	Good to excellent
FLAMMABILITY	UL 224	VW-1
PEEL STRENGTH OF METABLE LINER	ASTM 2671	> 80
COPPER CORROSION	UL 224	No corrosion



features:

SHRINK RATIO:	3:1
MATERIAL:	Polyolefin adhesive
FLAMMABILITY:	VW-1

- Excellent acid fastness and corrosion resistance
- UL and RoHS compliant
- Halogen free

CROSS REFERENCE TABEL :

Fabric Partnr.	WT ARTIKELNUMMER			Inch maat	KRIMP in MM		Inhoud					
	Industrial pack Fabric pack	WT system Retail pack	WT system Small pack		Voor	Na	I-pack/pcs Pack Carton		R-pack/pcs Pack Carton		S-pack/pcs Pack Carton	
712001BB		CU31RWTZW000300M0005	x	1/8	3.2	1.1			1x5.0 M	36x		
712002BB		CU31RWTZW000480M0004	x	3/16	4.8	1.6			1x4.0 M	36x		
712003BB		CU31RWTZW000600M03.5	x	1/4	6.4	2.2			1x3.5 M	36x		
712005BB		CU31RWTZW000900M0003	x	3/8	9.5	3.2			1x3.0 M	36x		
712006BB		CU31RWTZW001200M02.5	x	1/2	12.7	4.3			1x2.5 M	36x		
712007BB			x	5/8	15.9	5.3				36x		
712008BB		CU31RWTZW001800M0002	x	3/4	19.1	6.4			1x2.0 M	36x		
712009BB		CU31RWTZW002400M01.5	x	1	25.4	8.5			1x1.5 M	36x		

Kleuren zijn op aanvraag leverbaar.



GEBRUIK DEZE GEREEDSCHAPPEN :

